

FPRO Flexible Powered Roller Conveyor (50Kg/m)

O Belt for Roller Driving



PRODUCTS DETAILS



Each legs with handle for easy movement

Use 5mm high quality O ring PU belt

Dia 50*1.5mm galvanized steel roller

Each section with one 90W/120W Motor



Strong Casters With 4 bolts



3.5mm thickness galvanized curved side links plate



The control box with inverter to adjust speed.



FPRO Series Flexible Powered Roller Conveyor

Roller Drive Belt	5mm O Ring PU Drive Belt
Conveyor Roller	Diameter 50*1.5mm galvanized steel roller, Max. gap 130mm center to center
Drive Motor	90W mini motor
Join Frame	3.5mm thickness galvanized curved join plates with better loading capacity
Supporting Leg	32×32 powder coated tube with 25x25 galvanized tube inside
Max. Bearing Capacity	50Kg/m
Caster	Diameter 125mm high quality swivel lockable polyurethane casters
Control Box	Forward/Stop/Reverse
Frequency Inverter	~

Model	Open Length (mm)	Close Length (mm)	Width (mm)	Adjustable Height (mm)	Variable Speed (m/min)	Max. Load (kg/m ²)	Motor Power (w)
FPRO4	4800	1840	600, 700, 800	600-800	10-20	50	360
FPRO6	6000	2300	600, 700, 800	600-800	10-20	50	450
FPRO7	7200	2760	600, 700, 800	600-800	10-20	50	540
FPRO8	8400	3220	600, 700, 800	600-800	10-20	50	630
FPRO9	9600	3680	600, 700, 800	600-800	10-20	50	720
FPRO10	10800	4140	600, 700, 800	600-800	10-20	50	810
FPRO12	12000	4600	600, 700, 800	600-800	10-20	50	900
FPRO13	13200	5060	600, 700, 800	600-800	10-20	50	990
FPRO14	14400	5520	600, 700, 800	600-800	10-20	50	1080
FPRO15	15600	5980	600, 700, 800	600-800	10-20	50	1170
FPRO16	16800	6440	600, 700, 800	600-800	10-20	50	1260
FPRO18	18000	6900	600, 700, 800	600-800	10-20	50	1350
FPRO19	19200	7360	600, 700, 800	600-800	10-20	50	1440
FPRO20	20400	7820	600, 700, 800	600-800	10-20	50	1530