

# Truck Loading Unloading Conveyor

TLCP600/TLCP800



## PRODUCTS DETAILS



The front tongue conveyor can be removed when not use



Control Box: forward, stop, reverse, emergency stop, rise up and down



Front tongue conveyor with adjustable length and height.



5mm thick rough top PVC belt



Combine with flexible powered roller conveyor to reach close to the target



Side safety guide to prevent people down into the machine

## DATASHEET

### TLCP Truck Loading Conveyor-TLCP600 / TLCP800

#### Part 1: Inclined Belt Conveyor

Conveyor Belt Width	600mm or 800mm
Conveyor Belt Type	T=5mm rough top PVC belt
Adjustable Height	700-2500mm
Adjustable Speed	10-20m/min
Load Capacity	50kg/m
Belt Driven Motor	1.5kw
Conveyor Lift Motor	2.2kw
Frequency Inverter	Delta
Caster	Φ125mm heavy duty lockable swivel PU casters
Frame Construction	Carbon steel, powder coated in BLUE RAL 5015
Power Supply	220V/50Hz single phase, 380V/50Hz three phase

#### Part 2: Flexible Powered Roller Conveyor

Conveyor Roller	Φ50*T1.5mm galvanized steel rollers
Roller Drive Motor	60W/90W
Adjustable Speed	10-18m/min, two way
Load Capacity	50kg/m
Effective Width	600mm
Extendable Length	1800-4200mm
Adjustable Legs	30*30*2mm galvanized steel tubes or paint in black
Side Frame	X shape reinforced galvanized or painted steel plates
Castors	125mm (5") high quality swivel PU casters with brakes
Voltage	220V/50Hz single phase, 380V/50Hz three phase
Control Panel	Forward/Stop/Reverse, Emergency Stop, When rollers fully opened, carton length should be more than 280mm

## DATASHEET (TLCP600)

